



| | | |
|--|-------------------|--|
| Model | | HAWV28KR |
| Indoor unit | | HAWV28KR-I |
| Outdoor unit | | HAWV28KR-O |
| Type | | Reverse cycle |
| Rated values | | |
| Cooling Capacity | W | 8000 |
| Cooling Capacity Range | | 2300~8800 |
| Heating Capacity | W | 8000 |
| Heating Capacity Range | | 3000~10000 |
| Rated Input-Cooling | W | 2460 |
| Input-Cooling Range | W | 480~3400 |
| Rated Input-Heating | W | 2460 |
| Input-Heating Range | W | 600~4000 |
| Moisture Removal | L/Hour | 2.5 |
| Air Circulation (Super/High/High middle/ Middle/low middle/low/silent) | m ³ /h | 1250/1200/1050/1000/900/800/400 |
| Airflow distance | m | 14 |
| Airflow vertical swing angle | ° | 40 |
| Airflow horizontal deflection angle | ° | 140 |
| EER | | 3.25 |
| COP | | 3.25 |
| AEER | | 3.24 |
| ACOP | | 3.24 |
| Energy star rating for cooling - Hot | | 3 |
| Energy star rating for heating - Hot | | 3 |
| Energy star rating for cooling - Average | | 3 |
| Energy star rating for heating - Average | | 2.5 |
| Energy star rating for cooling - Cool | | 3 |
| Energy star rating for heating - Cool | | 1.5 |
| Outdoor temperature range | °C @ 30% humidity | -15 to +50 for cooling -15 to +24 for heating |
| Refrigerant | Type/kg | R32/1.58 |

| Noise | | |
|---|-----------------------|-------------------------------|
| Indoor unit (fan mode high) | dB (A) [S. pressure] | 47 |
| Indoor unit (fan mode silent) | dB (A) [S. pressure] | 32 |
| Outdoor unit | dB (A) [S. power] | 68 |
| Power Supply | | |
| Voltage, Frequency, Phase | | 220-240V/50Hz-1Ph |
| Rated current cooling | A | 11 |
| Current range cooling | A | 2.8~16.5 |
| Rated current heating | A | 11 |
| Current range heating | A | 3.3~18.5 |
| Locked rotor current | A | / |
| System | | |
| Compressor type/ drive | | Rotary |
| Expansion Device | | Electronic Expansion Valve |
| Evaporator | | Copper tube and Aluminium Fin |
| Condenser | | Copper tube and Aluminium Fin |
| Piping | | |
| Liquid pipe diameter | inch | 3/8 |
| Gas pipe diameter | inch | 5/8 |
| Maximum piping length/ height | m | 40/20 |
| Pre-charged length | m | 5 |
| Features | | |
| 3 DC motors (Indoor fan, outdoor fan, compressor) | | Yes |
| Vertical auto-swing louver | | Yes |
| Horizontal auto-swing louver | | Yes |
| Hidden display | | Yes |
| LCD wireless remote controller | | Yes |
| Removable and washable panel | | Yes |
| Washable PP filter | | Yes |
| 24 hours timer | | Yes |
| 5 speed and Auto indoor fan control | | Yes |
| Dimmer | | Yes |
| Sleep operation | | Yes |
| Smart function | | Yes |
| Super function | | Yes |
| Auto-restart | | Yes |
| Self-cleaning evaporator and condenser | | Yes |
| Hi-Nano ion air purification | | Yes |
| Silver ion filter | | Yes |
| Wi-Fi connectivity - 2.4GHz | 802.11 b/ g/ n | Yes |
| Google Assistant voice control | | Yes |
| ConnectLife control application | Android/ iOS | Yes/ Yes |
| Dimensions | | |
| Net dimensions indoor unit | [WxHxD] mm | 1213×238×315 |
| Net dimensions outdoor unit | [WxHxD] mm | 900×750×340 |
| Net weight indoor unit | kg | 13.5 |
| Net weight outdoor unit | kg | 52 |
| Packing dimensions indoor unit | [WxHxD] mm | 1289×392×318 |
| Packing dimensions outdoor unit | [WxHxD] mm | 1060×820×450 |
| Gross weight indoor unit | kg | 17 |

| | | |
|---------------------------|----|----|
| Gross weight outdoor unit | kg | 56 |
|---------------------------|----|----|